



PRODUCT SAFETY INFORMATION SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

TRADE NAME: PORON® XRD Urethanes
CHEMICAL FAMILY: Urethane Polymer
HMIS RATING: H 0 F 1 R 0
USE OF ARTICLE: Insulation, Gasket and Padding
DATE ISSUED: March 9, 2015
COMPANY/UNDERTAKING IDENTIFICATION: Rogers Corporation
245 Woodstock Road
Woodstock, CT 06281
Phone: 001-860-928-3622
Fax: 001-860-928-7843
Email: msdsinfo@rogerscorporation.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

CLASSIFICATION OF THE MATERIAL: NE
LABELING REQUIREMENTS: NE
EFFECTS OF OVEREXPOSURE: None are expected with normal handling. Cutting and other finishing operations may create polyurethane dust. Ventilation and personnel protection should be similar to all operations generating nuisance dust.
INHALATION: Dust may cause respiratory irritation. Remove to fresh air and seek medical attention if necessary.
EYE CONTACT: Dust may cause irritation. Flush eyes with water and seek medical attention if necessary.
SKIN CONTACT: Dust may cause irritation. Wash thoroughly with soap and water.
INGESTION: None known.
CHRONIC: NE

3. HAZARDS IDENTIFICATION

This material is produced as an "article" as defined in 20 CFR 1910.1200 and REGULATION (EC) N° 1907/2006 is therefore exempt from the Hazard Communication Standard and REACH. Since this material does not release and will not result in exposure to a hazardous chemical under normal conditions of use, no Safety Data Sheet is required.

<u>Chemical Name</u>	<u>CAS No.</u>	<u>EINECS /ELINCS</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>China OEL</u>	<u>EU Classification</u>
Alumina Trihydrate	21645-51-2	244-492-7	<20	15 mg/m ³ (Total Dust)	10 mg/m ³ (as AL)	NE	Not Classified Under 67/548/EC

4. FIRST-AID MEASURES

INHALATION:	Remove to fresh air. Obtain medical attention if symptoms persist.
EYE CONTACT:	Flush eyes with large amounts of water for 15 to 20 minutes. Obtain medical attention if symptoms persist.
SKIN CONTACT:	Immediately take off all contaminated clothing and flush area with water for 15 to 20 minutes. Obtain medical attention if symptoms persist.
INGESTION:	NA

5. FIRE-FIGHTING MEASURES

FLASH POINT:	NE °C (°F)	Flammable Limits:	LEL	NA	UEL	NA
AUTOIGNITION TEMPERATURE:	NE °C (°F)					
EXTINGUISHING MEDIA:	<u>X</u> Water Spray	<u>X</u> Foam	<u>X</u>	CO ₂		
	<u>X</u> Dry Chemical	<u>X</u> Other –				
SPECIAL FIRE FIGHTING PROCEDURES:	Decomposition in a fire may produce toxic fumes. Firefighters should be equipped with self-contained breathing apparatus and turnout gear.					
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Polyurethane materials may generate dense smoke in a fire.					

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:	None needed.
ENVIRONMENTAL PRECAUTIONS:	None needed.
CLEANING METHODS:	Sweep or shovel into appropriate container for disposal. Avoid creation of nuisance dust.

7. HANDLING AND STORAGE

HANDLING:	Hot wire cutting operations should be exhausted to prevent exposure to irritating vapors. Wear suitable protective equipment, refer to Section 8.
STORAGE:	Keep in a cool, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:	None needed under normal conditions. If material is heated and odors are noticeable and/or irritating a respirator meeting NIOSH requirements should be used. A qualified individual should evaluate each situation.
<u>VENTILATION</u>	
LOCAL:	Recommended for all industrial operations.
GENERAL:	Recommended for all industrial operations.
<u>PERSONAL PROTECTION</u>	
HAND:	Gloves to avoid skin contact if desired.
EYE:	Safety glasses with side-shields are recommended in all industrial operations
SKIN:	None Required
OTHER:	Safety shower/eyewash in the area.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Solid, Cellular Urethane Foam Roll or Sheet (Various Colors Available)
ODOR:	Slight Odor
PHYSICAL STATE:	Solid
BOILING POINT:	NA °C (°F)
MELTING POINT:	NE °C (°F)
FREEZING POINT:	NA °C (°F)
FLASH POINT:	NE °C (°F)
WATER SOLUBILITY:	In-Soluble
VAPOR DENSITY:	NA
VAPOR PRESSURE:	NA
SPECIFIC GRAVITY:	0.2-0.53 (Water = 1)
PARTITION COEFFICIENT:	NA
EVAPORATION RATE:	NA
RELATIVE DENSITY:	NA
VISCOSITY:	NA
AUTO-IGNITION TEMPERATURE:	NA °C (°F)
DECOMPOSITION TEMPERATURE:	NA °C (°F)
PH:	NA
FLAMMABILITY:	NA

10. STABILITY AND REACTIVITY

STABLE UNSTABLE

CONDITIONS TO AVOID:	NE
MATERIALS TO AVOID:	NE
HAZARDOUS POLYMERIZATION:	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Does Not Occur
HAZARDOUS DECOMPOSITION PRODUCTS:	CO, CO ₂ , Oxides of nitrogen, HCN, and traces of incompletely burned carbon compounds.

11. TOXICOLOGICAL INFORMATION

CARCINOGENIC STATUS: NA

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NA

13. DISPOSAL CONSIDERATION

PHYSICAL/CHEMICAL PROPERTIES AFFECTING DISPOSAL:	None
ENVIRONMENTAL TOXICITY DATA:	NA
WASTE DISPOSAL METHOD:	Dispose of in accordance with applicable federal, state, provincial, and local laws and regulations.

14. TRANSPORT INFORMATION

UN NUMBER:	Not Regulated
UN PROPER SHIPPING NAME:	Not Regulated
HAZARD CLASS (ES):	Not Regulated
PACKING GROUP:	Not Regulated
ENVIRONMENTAL HAZARDS:	NE

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS:

Canadian (DSL/NDSL):	Listed
Australian (ACIS):	NE
Korea (KECI):	NE
Japan (ENCS, MITI):	NE
China (IESCS)	Article - exempt
EU Directive 2011/65/EC (RoHS):	Does not contain any intentionally added substances mentioned by the RoHS directive.
European: Symbol	Not classified according to directive 1999/45/EC & 2001/60/EC(dangerous preparations).
R-Phase(s):	NA
S-Phase(s):	NA
TSCA (Toxic Substances Control Act):	All materials are listed or exempt from TSCA listing.
CERCLA (Comprehensive Emergency Response, Compensation, and Liability Act):	NA
SARA TITLE III (Superfund Amendments and Reauthorization Act):	NA
311/312 HAZARD CATEGORIES:	None

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS #
NA

CHEMICAL NAME
NA

PERCENT BY WEIGHT
NA

16. OTHER INFORMATION

NA = Not Applicable
NE = Not Established
NC = Not Classified

FILE: 99230-PORON XRD Urethanes PSIS-03092015.doc

PREPARED BY: Michal Werbecki
REVIEWED BY: Curtis Kempton

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF.

ROGERS CORPORATION ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.