



Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

570.000 Renia - Primer for PUR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Isocyanate containing product.
Coatings and paints, fillers, putties, thinners

1.3. Details of the supplier of the safety data sheet

Company name:	Renia Gesellschaft mbH. Chemische Fabrik	
Street:	Ostmerheimer Straße 516	
Place:	D-51109 Köln (Cologne)	
Post-office box:	910659 D-51076 Köln (Cologne)	
Telephone:	+49-221-630799-0	Telefax: +49-221-630700-50
e-mail:	info@renia.com	
Contact person:	Heinz Buchholz Dipl.Chem	Telephone: 16
e-mail:	labor@renia.com	
Internet:	www.renia.com	
Responsible Department:	Labor 07:30 - 16:00 Uhr	

1.4. Emergency telephone number:

+49-221-630799-0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: F - Highly flammable, Xi - Irritant

R phrases:

Highly flammable.

Irritating to eyes.

May cause sensitisation by skin contact.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Classification according EC regulation 1272/2008 (CLP):

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 2 of 12

Hazardous components which must be listed on the label

ethyl acetate

Signal word:

Danger

Pictograms:

GHS02-GHS07



Hazard statements

- H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use ... to extinguish.
P235 Keep cool.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container to

Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.
EUH208 Contains 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate. May produce an allergic reaction.

Additional advice on labelling

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Contains isocyanates. See information supplied by the manufacturer.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 3 of 12

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Coatings and paints, fillers, putties, thinners
Isocyanate containing product.

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
205-500-4	ethyl acetate	80-100 %
141-78-6	F - Highly flammable, Xi - Irritant R11-36-66-67	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
01-2119475103-46		
	Aromatisches Isocyanat	5-20 %
9017-01-0	R43	
247-722-4	4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate	<0,1 %
26471-62-5	Carc. Cat. 3, T+ - Very toxic, Xi - Irritant R40-26-36/37/38-42/43-52-53	
615-006-00-4	Carc. 2, Acute Tox. 2, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Resp. Sens. 1, Skin Sens. 1, Aquatic Chronic 3; H351 H330 H319 H335 H315 H334 H317 H412	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Grease skin after contact.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 4 of 12

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder. alcohol resistant foam. ABC powder. Atomized water. Dry sand.

Unsuitable extinguishing media

Water. High power water jet. High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Carbon monoxide. Hydrocyanic acid (hydrocyanic acid). vapours of isocyanate

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Special exposure hazards arising from the substance itself, combustion products, resulting gases: In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. If handled uncovered, arrangements with local exhaust ventilation should be

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 5 of 12

used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharge. Vapours can form explosive mixtures with air. Keep away from sources of ignition. - No smoking. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours / aerosols must be extracted by suction immediately at point of origin.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feeding stuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean.
Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

Coatings and paints, fillers, putties, thinners

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Before starting work, apply solvent-resistant skincare preparations.

Eye/face protection

Suitable eye protection: goggles.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 6 of 12

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Test suitability of gloves before use.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Environmental exposure controls

Do not allow to enter into soil/subsoil. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	light yellow
Odour:	ester

Test method

pH-Value: Test not required.

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	77 °C DIN 53 171
Flash point:	-4 °C DIN 51 755

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	11,5 vol. %
Ignition temperature:	460 °C DIN 51 794

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: (at 20 °C)	97 hPa DIN EN 12
Density (at 20 °C):	0,9 g/cm ³ DIN 51 757
Water solubility:	Decomposes in contact with water.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 7 of 12

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:

DIN 51550

(at 20 °C)

Flow time:

< 30 (3 mm)

Vapour density:

not determined

Evaporation rate:

not determined

Solvent separation test:

< 0,1 %

Solvent content:

87,5 %

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard. Explosive. The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.2. Chemical stability

Danger of polymerisation. The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions. Gas/vapour, highly flammable.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Risk of explosion by shock, friction, fire or other sources of ignition. Remove all sources of ignition. Keep away from heat. Ignition hazard. Decomposition takes place from temperatures above: > 150 °C

10.5. Incompatible materials

Keep away from: Protect against: Contact with air/oxygen. Acid, concentrated. , Oxidizing agents, strong.

Reacts violently in contact with acids, amines, driers, polymerization accelerators and easily oxidized materials.

Radical former, Peroxide, Reducing agent.

10.6. Hazardous decomposition products

Hydrogen cyanide (hydrocyanic acid). Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

There are no data available on the preparation/mixture itself.

Acute toxicity

Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis .

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 8 of 12

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
141-78-6	ethyl acetate	oral	LD50	5600 mg/kg	Ratte	
		dermal	LD50	18000 mg/kg	Kaninchen	
		inhalative (4 h) vapour	LC50	58 mg/l	Ratte	
26471-62-5	4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate	inhalative vapour	ATE	0,5 mg/l		
		inhalative aerosol	ATE	0,05 mg/l		

Irritation and corrosivity

May cause skin and eye irritation in susceptible persons. Contact with eyes may cause irritation.

Sensitising effects

There are no data available on the preparation/mixture itself.

STOT-single exposure

There are no data available on the preparation/mixture itself.

Severe effects after repeated or prolonged exposure

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Inhalation causes narcotic effects/intoxication.

Carcinogenic/mutagenic/toxic effects for reproduction

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

LD50/oral/rat = > 2000 mg/kg
Mild eye irritation (rabbit)

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

When under water, the product is transformed to poly-urea at the interface while producing CO₂. Liquid soap or water soluble solvents enhance this reaction strongly.

CAS No	Chemical name	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
141-78-6	ethyl acetate	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	
		Acute algae toxicity	ErC50	3300 mg/l	72 h	Scenedesmus subspicatus	
		Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

The product has not been tested. Product is biodegradable with difficulty.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,60

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 9 of 12

12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

12.6. Other adverse effects

Toxic to aquatic life with long lasting effects.

Further information

Avoid release to the environment. The statement is derived from the properties of the components.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethyl acetate)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	640D
Limited quantity:	LQ4, 3 Liter
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Other applicable information (land transport)

: 274 - 330 - 601 - 640D
: 2

Inland waterways transport (ADN)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (ethyl acetate)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 10 of 12



Classification code: F1
Special Provisions: 640D
Limited quantity: 1 Liter

Other applicable information (inland waterways transport)

E2

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethyl acetate)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 Liter
EmS: F-E, S-E

Other applicable information (marine transport)

Staukategorie B

Air transport (ICAO)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ethyl acetate)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2
: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable



Safety Data Sheet

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 11 of 12

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 99,92 % (899,28 g/l)

2004/42/EC (VOC): 99,92 % (899,28 g/l)

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

National regulatory information

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 1 - slightly water contaminating

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant R-phrases (Number and full text)

- 11 Highly flammable.
- 26 Very toxic by inhalation.
- 36 Irritating to eyes.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 40 Limited evidence of a carcinogenic effect.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 43 May cause sensitisation by skin contact.
- 52 Harmful to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

Relevant H- and EUH-phrases (Number and full text)

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

570.000 Renia - Primer for PUR

Print date: 15.11.2014

Product code: 570.000

Page 12 of 12

EUH204

Contains isocyanates. May produce an allergic reaction.

EUH208

Contains 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)