

MATERIAL SAFETY DATA SHEET

Section 1 Chemical Product and Company Information

Manufacturer: Baycomp
5035 North Service Road, Bldg. A-1,
Burlington, Ontario L7L 5V2
Canada

Telephone Number: (905) 332-0991
Fax Number: (905) 332-0433

Revision Date: November 20, 2013

Product Identification: XT Sprint Continuous Fiber Reinforced Thermoplastic (CFRT)
XT-Ease Flex, Semi Flex, Semi Rigid, Medium Rigid,
Rigid and Ultra Rigid

Section 2 Composition and Content

Glass fibers impregnated with polypropylene (PP) resin. Fibers configure in biaxial directions, encapsulated homogeneously with PP resin and formed into continuous fiber reinforced thermoplastic panels.

Component	Cas#	% by Weight	TLV	PEL
Glass Fiber	65997-17-3	60	5 mg/m ³	15 mg/m ³
Polypropylene	9010-79-1	40	N/A	N/A

Section 3 Hazards Identification

As is, this product should not be considered hazardous. Glass fibers are bonded to the polymer and do not generate quantities of dust or particulate.

Once a part has been formed, cutting, grinding or sanding may be required. Avoid breathing fibers or dust generated by cutting, grinding or sanding. Do not allow eye or skin contact.

If heating, cutting, grinding or sanding of the material is to take place, then the following precautions should be noted.

Section 4
First Aid Measures

Inhalation:	Remove to a well ventilated area. Get medical attention if irritation develops or persists.
Eye Irritation:	Flush eyes out thoroughly with water. Get medical attention.
Skin Irritation :	Wash affected area thoroughly with water. Get medical attention if irritation develops or persists. If hot or molten material burns skin, immerse the burned area in cold running water and obtain medical attention immediately.

Section 5
Fire Fighting Measures

Auto Ignition Temperature:	380°C (716°F) Attributed to the polymer component.
Extinguishing Media:	Water fog, carbon dioxide, dry chemical foam.
Special Fire Fighting Procedure:	Standard procedures for class A fires, use self containing breathing apparatus.

Section 6
Accidental Release Measures

If the material comes in contact with the floor or becomes dirty from dust, it can be wiped and used as is as long as it has not become contaminated.

Section 7
Handling and Storing

Adequate ventilation and gloves should be provided during handling. Store at room temperature and at a moderate humidity level.

Section 8
Exposure Controls/Personal Protection

Appropriate Hygienic Practices:	Do not allow eye or skin contact. Avoid breathing fibers that may be exposed. Wash thoroughly after handling and before eating, drinking or smoking.
Personal Protective Equipment:	Use gloves to reduce skin irritation or burns during processing. Safety glasses. Appropriate protective clothing.

Section 9
Physical and Chemical Properties

Physical State:	Solid
Appearance:	Decorative
Odor:	None
Specific Gravity:	1.35 - 1.45 g/cm ³
Melting Point:	168°C (334°F)
Processing Temperature:	210°C (410°F)
Solubility in Water:	Negligible
% Volatile:	Less than 0.5%
Boiling Point:	N/A
Vapor Pressure @ 20°C:	N/A
Vapor Density:	N/A
Evaporation Rate:	N/A
PH:	N/A

Section 10
Stability and Reactivity

Chemical Stability:	Stable
Corrosivity:	Not corrosive
Hazardous Polymerization:	Will not occur
Conditions to Avoid:	Avoid prolonged exposure to temperatures above the recommended processing temperature. Above 250 to 280°C, polypropylene may degrade and may cause irritation to the eyes and respiratory tract. Avoid contact with strong oxidizing agents and hot or concentrated acids.

**Section 11
Toxicological Information**

No medical-scientific data has been established to classify glass impregnated with polypropylene as carcinogenic to humans.

**Section 12
Ecological Information**

No ecological information exists on this product. Not expected to present any significant ecological problem.

**Section 13
Disposal Information**

The waste material of this product is not expected to be hazardous. Sanitary land fill is recommended. Disposal must be done in accordance with relevant regulations.

**Section 14
Transportation Information**

This product is not regulated as dangerous or hazardous goods therefore, no hazard identification is required.

**Section 15
Regulatory Information**

BayComp complies with the regulation of the Workplace Hazardous Materials Information System (WHMIS).

**Section 16
Other Information**

The information contained herein is furnished without warranty of any kind. Product users should make independent judgments of suitability of this information to ensure proper use and protect the health and safety of employees.